



M14D 系列产品

型号	规定电流下的电压	最大允许工作电压		最大限制电压 (8/20 μs)		能量耐量 10/1000 μs		通流容量 (8/20 μs)		静态容量 @ 1KHz	最大静态功率	安规认证			
		V1mA (V)	AC (V)	DC (V)	Vc (V)	Ip (A)	(J)	(J)	(A)			(A)	(pF)	(W)	UL
M14D151T136	150 (135~165)	95	125	250	50	35	50	6000	3000	1300	0.6		●		●
M14D181T136	180 (162~198)	115	150	300	50	43.4	58	6000	3000	1100	0.6		●		●
M14D201T136	200 (185~225)	130	170	340	50	49	70	6000	3000	1000	0.6	●	●		●
M14D221T136	220 (198~242)	140	180	360	50	56	78	6000	3000	900	0.6	●	●	●	●
M14D241T136	240 (216~264)	150	200	395	50	70	85	6000	3000	830	0.6	●	●	●	●
M14D271T136	270 (243~297)	175	225	455	50	77	100	6000	3000	740	0.6	●	●	●	●
M14D301T136	300 (270~330)	190	250	500	50	84	107	6000	3000	670	0.6	●	●	●	●
M14D331T136	330 (297~363)	210	275	550	50	91	115	6000	3000	610	0.6	●	●	●	●
M14D361T136	360 (324~396)	230	300	595	50	98	125	6000	3000	560	0.6	●	●	●	●
M14D391T136	390 (351~429)	250	320	650	50	105	140	6000	3000	510	0.6	●	●	●	●
M14D431T136	430 (387~473)	275	350	710	50	112	155	6000	3000	460	0.6	●	●	●	●
M14D471T136	470 (423~517)	300	385	775	50	119	175	6000	3000	430	0.6	●	●	●	●
M14D511T136	510 (459~561)	320	415	845	50	119	190	6000	3000	390	0.6	●	●	●	●
M14D531T136	530 (477~583)	340	445	870	50	119	150	6000	5000	385	0.6				
M14D561T136	560 (504~616)	350	460	925	50	119	200	6000	3000	360	0.6	●	●	●	●
M14D621T136	620 (558~682)	385	505	1025	50	119	210	6000	3000	320	0.6	●	●	●	●
M14D681T136	680 (612~748)	420	560	1120	50	126	220	6000	3000	290	0.6	●	●	●	●
M14D751T136	750 (675~825)	460	615	1240	50	140	225	6000	3000	270	0.6	●	●	●	●

M20D 系列产品

型号	规定电流下的电压	最大允许工作电压		最大限制电压 (8/20 μs)		能量耐量 10/1000 μs		通流容量 (8/20 μs)		静态容量 @ 1KHz	最大静态功率	安规认证			
		V1mA (V)	AC (V)	DC (V)	Vc (V)	Ip (A)	(J)	(J)	(A)			(A)	(pF)	(W)	UL
M20D151T136	150 (135~165)	95	125	250	100		50	10000	5000	2700	1.0	●	●	●	●
M20D181T136	180 (162~198)	115	150	300	100		58	10000	5000	2200	1.0	●	●	●	●
M20D201T136	200 (185~225)	130	170	340	100		70	10000	5000	2000	1.0	●	●	●	●
M20D221T136	220 (198~242)	140	180	360	100		78	10000	5000	1800	1.0	●	●	●	●
M20D241T136	240 (216~264)	150	200	395	100		85	10000	5000	1650	1.0	●	●	●	●
M20D271T136	270 (243~297)	175	225	455	100		100	10000	6000	1500	1.0	●	●	●	●

M20D301T136300(270~330)	190	250	500	100		107	10000	5000	1300	1.0	●	●	●	●
M20D331T136330(297~363)	210	275	550	100		115	10000	5000	1200	1.0	●	●	●	●
M20D361T136360(324~396)	230	300	595	100		125	10000	5000	1100	1.0	●	●	●	●
M20D391T136390(351~429)	250	320	650	100		140	10000	5000	1000	1.0	●	●	●	●
M20D431T136430(387~473)	275	350	710	100		155	10000	5000	930	1.0	●	●	●	●
M20D471T136470(423~517)	300	385	775	100		175	10000	5000	850	1.0	●	●	●	●
M20D511T136510(459~561)	325	415	845	100		190	10000	5000	780	1.0	●	●	●	●
M20D561T136560(504~616)	350	460	925	100		200	10000	6000	710	1.0	●	●	●	●
M20D621T136620(558~682)	385	505	1025	100		210	10000	5000	650	1.0	●	●	●	●
M20D681T136680(612~748)	420	560	1120	100		220	10000	5000	600	1.0	●	●	●	●
M20D751T136750(675~825)	460	615	1240	100		225	10000	5000	530	1.0	●	●	●	●

M20S 系列产品

型号	规定电流下的电压	最大允许工作电压		最大限制电压 (8/20 μ s)		能量耐量 10/1000 μ s		通流容量 (8/20 μ s)		静态电容 量 @ 1KHz	最大静态 功率	安规认证			
	V1mA(V)	AC (V)	DC(V)	Vc(V)	Ip(A)	(J)	(J)	(A)	(A)	(pF)	(W)	UL	TUV	CUL	PSE
M20S151T136150(135~165)	95	125	250	115		127	15000	7500	3200	1.0	●	●	●	●	
M20S181T136180(162~198)	115	150	300	115		156	15000	7500	2650	1.0	●	●	●	●	
M20S201T136200(185~225)	130	170	340	115		170	15000	7500	2400	1.0	●	●	●	●	
M20S221T136220(198~242)	140	180	360	115		185	15000	7500	2160	1.0	●	●	●	●	
M20S241T136240(216~264)	150	200	395	115		200	15000	7500	2000	1.0	●	●	●	●	
M20S271T136270(243~297)	175	225	455	115		230	15000	7500	1800	1.0	●	●	●	●	
M20S301T136300(270~330)	190	250	500	115		250	15000	7500	1560	1.0	●	●	●	●	
M20S331T136330(297~363)	210	275	550	115		270	15000	7500	1440	1.0	●	●	●	●	
M20S361T136360(324~396)	230	300	595	115		305	15000	7500	1320	1.0	●	●	●	●	
M20S391T136390(351~429)	250	320	650	115		330	15000	7500	1200	1.0	●	●	●	●	
M20S431T136430(387~473)	275	350	710	115		365	15000	7500	1160	1.0	●	●	●	●	
M20S471T136470(423~517)	300	385	775	115		420	15000	7500	1020	1.0	●	●	●	●	
M20S511T136510(459~561)	320	415	845	115		430	15000	7500	935	1.0	●	●	●	●	
M20S561T136560(504~616)	350	460	925	115		455	15000	7500	850	1.0	●	●	●	●	
M20S621T136620(558~682)	385	505	1025	115		465	15000	7500	780	1.0	●	●	●	●	
M20S681T136680(612~748)	420	560	1120	115		480	15000	7500	720	1.0	●	●	●	●	
M20S751T136750(675~825)	460	615	1240	115		500	15000	7500	635	1.0	●	●	●	●	